



KRIWAN

INT276 LC+® Level monitor

INT276 LC+®

Technical specifications

Supply voltage	
- 52 S 476 ...	AC 50/60Hz 230V ±10% 3VA
- 41 S 476 ...	AC 50/60Hz 115V ±10% 3VA
Permitted ambient temperature	-30...+60°C
Medium temperature	Max. +120°C (<1h) Max. +100°C
Permitted rel. humidity	10-95% r. h. no condensation
Switch delay	
- After applying the supply voltage	3s ±1s
- Level missing or fault	5s ±2s
- Level good and no fault	5s ±2s
Relay	
- Contact	AC 240V 2.5A C300 at least AC/DC 24V 20mA
- Mechanical service life	Approx. 1 million switching cycles
Protection class acc. to EN 60529	IP54 in mounted condition
Connection type	Cable 4 x AWG 18/7
Housing material	PA glass-fibre-reinforced
Mounting	Union nut (torque max. 10Nm)
Dimensions	Refer to dimensions in mm
Weight	Approx. 160g
Check base	EN 61000-6-2, EN 61000-6-3 EN 61010-1 Overvoltage category II Pollution level 2
Approval	UL File No. E222056 „UR _{us}

Order data

INT276 LC+ Level monitor (AC 230V)	52 S 476 S62
INT276 LC+ Level monitor (AC 115V)	41 S 476 S62
Accessories and application information	see www.kriwan.com