

Intelligent toilet series (water treatment equipment) 智能马桶系列 (水处理设备)



Type: TXW-080

Features:

Applied PSB-5 type element and encapsulated by designed stainless steel tube. Extremely fast response. Good humidity resist.

Applications:

IH toilet, water treatment equipment.

Temperature Range:

-20°C ~ 100°C

Thermal time constant:

Approx. 0.3sec. (in warm water)

类型: TXW-080

特点:

极速反应型, 异形不锈钢拉伸管结构的温度传感器。使用PSB-S5型热敏电阻, 高响应速度, 防湿性强。

用途:

智能马桶, 水处理设备。

使用温度范围:

-20°C ~ 100°C

热时间常数:

约0.3秒 (在温水里)



Type: TXW-081

Features:

Applied PSB-S3 type element and encapsulated by designed stainless steel tube sealed with epoxy. Good in response and humidity resist. Custom design for the mounting bracket is acceptable.

Applications:

IH toilet, water treatment equipment.

Temperature Range:

-40°C ~ 100°C

Thermal time constant:

Less than. 1sec. (in warm water)

类型: TXW-081

特点:

PSB-S3型热敏电阻和环氧树脂封装的不锈钢保护管结构。反应速度快, 耐湿性强, 安装片可根据要求更改。

用途:

智能马桶, 水处理设备及各种管道等。

使用温度范围:

-40°C ~ 100°C

热时间常数:

小于1秒 (在温水里)



Type: TXW-082

Features:

Applied PSB-S3 type element and encapsulated by designed stainless steel tube sealed with epoxy. Good in response and humidity resist. Custom design for the mounting bracket is acceptable.

Applications:

IH toilet, water treatment equipment.

Temperature Range:

-40°C ~ 100°C

Thermal time constant:

Less than. 1sec. (in warm water)

类型: TXW-082

特点:

PSB-S3型热敏电阻和环氧树脂封装的不锈钢保护管结构。反应速度快, 耐湿性强, 安装片可根据要求更改。

用途:

智能马桶, 水处理设备及各种管道等。

使用温度范围:

-40°C ~ 100°C

热时间常数:

小于1秒 (在温水里)